

Very preliminary reference Moon model

Raphaël Garcia, Jeannine Gagnepain-Beyneix, Sébastien Chevrot, Philippe Lognonné

▶ To cite this version:

Raphaël Garcia, Jeannine Gagnepain-Beyneix, Sébastien Chevrot, Philippe Lognonné. Very preliminary reference Moon model. Physics of the Earth and Planetary Interiors, 2011, 188 (1-2), pp.96-113. 10.1016/j.pepi.2011.06.015 . hal-03964140

HAL Id: hal-03964140 https://u-paris.hal.science/hal-03964140v1

Submitted on 2 Feb 2023

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Very Preliminary Reference Moon Model

Raphaël F. Garcia^{a,b}, Jeannine Gagnepain-Beyneix^c, Sébastien Chevrot^{a,b},
 Philippe Lognonné^c

^aUniversité de Toulouse; UPS-OMP; IRAP; Toulouse, France

^bCNRS; IRAP; 14, avenue Edouard Belin, F-31400 Toulouse, France

^cEquipe Géophysique Spatiale et Planétaire, Institut de Physique du Globe, Sorbonne

Paris Cité, Univ Paris Diderot, UMR 7154 CNRS, 4 ave de Neptune F-94100 Saint Maur des Fossés, France

9 Abstract

The deep structure of the Moon is a missing piece to understand the forma-10 tion and evolution of the Earth-Moon system. Despite the great amount of 11 information brought by the Apollo passive seismic experiment (ALSEP), the 12 lunar structure below deep moonquakes, which occur around 900 km depth, 13 remains largely unknown. We construct a reference Moon model which in-14 corporates physical constraints, and fits both geodesic (lunar mass and polar 15 moment of inertia, and Love numbers) and seismological (body wave arrivals 16 measured by Apollo network) data. In this model, the core radius is con-17 strained by the detection of S waves reflected from the core. In a first step, 18 for each core radius, a radial model of the lunar interior, including P and 19 S wave velocities and density, is inverted from seismic and geodesic data. 20 In a second step, the core radius is determined from the detection of shear 21 waves reflected on the lunar core by waveform stacking of deep moonquake 22 Apollo records. This detection has been made possible by careful data selec-23 tion and processing, including a correction of the gain of horizontal sensors 24 based on the principle of energy equipartition inside the coda of lunar seismic 25 records, and a precise alignment of SH waveforms by a non-linear inversion 26 method. The Very Preliminary REference MOON model (VPREMOON) 27 obtained here has a core radius of 380 ± 40 km and an average core mass den-28 sity of 5200 ± 1000 kg/m³. The large error bars on these estimates are due 29 to the poorly constrained S-wave velocity profile at the base of the mantle 30 and to mislocation errors of deep moonquakes. The detection of horizontally 31 polarized S waves reflected from the core and the absence of detection of 32 vertically polarized S waves favour a liquid state in the outermost part of the 33

Preprint submitted to Physics of the Earth and Planetary Interiors May 18, 2011

1

4

5

6

7

8

³⁴ core. All these results are consistent, within their error bars, with previous
³⁵ estimates based on lunar rotation dissipation (Williams et al., 2001) and on
³⁶ lunar induced magnetic moment (Hood et al., 1999).

37 Keywords: Moon, Seismology, Internal Structure, Core, Seismic Body

38 Waves

39 1. Introduction

The radius of Earth's core has been relatively precisely determined more 40 than one century ago from the analysis of seismic data (Oldham, 1914), only 41 17 years after the first measurement on a seismogram (von Rebeur-Paschwitz, 42 1889). But more than 40 years of negative attempts and processing efforts 43 have been necessary before the publication of the first reported observations 44 of seismic core phases in the Apollo seismic data (Weber et al., 2011). How-45 ever, the results of this pioneering paper in which some inconsistency between 46 the discontinuity radii deduced from different boday waves remains, must be 47 confirmed by a more precise analysis which integrates the trade-off between 48 the mantle seismic velocities and the core size, and the constraints on the 49 body wave amplitudes. Note also that Love numbers were only computed a 50 posteriori and not integrated in the model inversion. As the radius of the core 51 is a key parameter for constraining scenarios of Moon formation by a giant 52 impact (Benz et al., 1989; Canup and Asphaug, 2001), its precise determina-53 tion will greatly improve our understanding of the geometry and dynamics 54 of such giant and catastrophic impact, providing crucial constraints on the 55 state of primordial Earth's mantle. Prior to Weber et al. (2011), none of the 56 published seismic models (Toksoz et al., 1974; Nakamura et al., 1976, 1982; 57 Khan and Mosegaard, 2002; Lognonné et al., 2003; Gagnepain-Beyneix et al., 58 2006; Khan et al., 2007) have put direct constraints on the lunar core radius, 59 and only indirect constraints were achieved. Those come from the observa-60 tions of magnetic signals related to the lunar's core magnetic field rejection 61 (Russell et al., 1982; Hood et al., 1999) and from the inversion of geode-62 tic data (Hood and Jones, 1987; Mueller et al., 1988; Kuskov and Kronrod, 63 1998; Kuskov et al., 2002), including the Love numbers (Williams et al., 2001; 64 Khan et al., 2004; Khan and Mosegaard, 2005). Among these constraints, 65 the difference between the spin of the polar axis and the Cassini spin state 66 measured by Williams et al. (2001) is central for suggesting a liquid core. So 67 far, the suggested values of this lunar liquid core radius range from 250 km 68

⁶⁹ to 450 km.

Constraints on the core composition are even much weaker, as the end 70 member values for its size lead to either pure iron core for the smallest values, 71 to ilmenite core for the largest ones (see for example Lognonné and Johnson 72 (2007) for the trade-off of core models verifying both the mantle seismic con-73 straints and the global geodetic ones). The seismically inverted temperature 74 at the bottom of the mantle provided by Gagnepain-Beyneix et al. (2006) 75 or Khan et al. (2007) are all lower than the pure iron liquidus temperature, 76 suggesting that some light elements must be present in the core if it is liquid. 77 These two models however neither include the Love numbers nor core seismic 78 phases, even though these two types of information could directly constrain 79 the size of the core in their inversions. 80

In this study, we investigate the seismic structure of the lunar interior fol-81 lowing a two-step approach. First, we construct a set of acceptable seismic 82 models of the Moon constrained by mass, moment of inertia, Love numbers 83 and arrival times of P and S waves measured by the Apollo passive seismic 84 experiment. Then, we estimate the core radius by detecting core reflected 85 S wave arrivals from waveform stacking methods. The final result is a pre-86 liminary reference model for the Moon, that includes the size and average 87 density of the core. 88

⁸⁹ 2. Construction of seismic moon models

This section describes the construction and selection of the best radial seismic lunar models. These models are described by a small number of parameters, respecting a set of a priori geophysical equations and fitting seismological and geodesic observations. The aim is to obtain the best physical models for each core radius and use them to detect core reflected phases.

95 2.1. A priori information

The radial models are constructed in order to fit exactly the lunar mass 96 $M_o = 7.3458 \times 10^{22}$ kg (Konopliv et al., 2001; Goossens and Matsumoto, 97 2008). The crustal model is extracted from Gagnepain-Beyneix et al. (2006) 98 seismic model (see figure 1). Crustal density (ρ_c) below the 1 km thick re-99 golith layer is assumed to be constant and allowed to vary in order to fit 100 geodesic observations. The strong degree one crustal thickness variation is 101 taken into account by assuming a Moho depth of 28 km below the Apollo 102 network (on the near side) in order to fit seismic observations, and an average 103



Figure 1: A priori crust model extracted from Gagnepain-Beyneix et al. (2006) assuming a constant density inside the crust below the 1 km thick regolith layer.

Moho depth of 40 km (Chenet et al., 2006) in order to fit geodesic observations. Studies of lunar gravity and topography constrain both the average crustal thickness and the density contrast between the crust and the mantle. However, these parameters are correlated. Assuming an average Moho depth of 40 km, the density contrast between crust and mantle is predicted to be about 0.55 (Chenet et al., 2006; Wieczorek et al., 2006). This value is taken as an a priori for the construction of the radial Moon models.

The lunar mantle is assumed to be homogeneous and without any phase 111 transition. This assumption is strong, but if the composition of the lunar 112 mantle is close to Earth's mantle, no phase change of major silicate con-113 stituents is expected in the pressure and temperature ranges of the Moon 114 mantle. In addition, previous investigations of lunar mantle chemistry based 115 on seismic data did not detect any strong chemical composition variation 116 with depth (Khan et al., 2007), suggesting that the 550 km depth discon-117 tinuity, reported in earlier models (Nakamura, 1983; Khan and Mosegaard, 118 2002), is weakly resolved by the Apollo data set (Lognonné and Johnson, 119 2007). In addition, we assume an adiabatic temperature gradient in the lu-120 nar mantle. Even if not fully valid in the middle and upper mantle, where the 12 temperature profile is mainly conductive (Gagnepain-Beyneix et al., 2006), 122

the adiabatic hypothesis is expected to generate no more than a few percent of differences in seismic velocities (Bina, 2003) which is smaller than the typical error of lunar seismic models. Assuming homogeneity and adiabaticity of the lunar mantle, we can use the Adams-Williamson equation to derive the density profile of the Moon mantle:

$$\frac{d\rho}{dr} = -\frac{\rho(r)g(r)}{\Phi(r)} \tag{1}$$

where r is the radius, $\rho(r)$ the volumic mass, g(r) gravity, and $\Phi(r)$ the seismic parameter given by:

$$\Phi(r) = V_P^2(r) - \frac{4}{3}V_S^2(r)$$
(2)

where $V_P(r)$ and $V_S(r)$ are respectively the P and S wave velocities. If we assume a state of hydrostatic equilibrium for the lunar interior, pressure variations are described by:

$$\frac{dP}{dr} = -\rho(r)g(r) \tag{3}$$

where P(r) is pressure.

Consequently, if seismic velocities are known, the above equations can be
integrated from top to bottom in order to construct gravity, pressure, and
density profiles, using the additional relation between gravity and density:

$$g(r) = \left(\frac{r_o}{r}\right)^2 g_o - \frac{4\pi G}{r_o^2} \left(\frac{r_o}{r}\right)^2 \int_r^{r_o} \rho(u) u^2 du \tag{4}$$

where G is the gravitational constant, r_o the average Moon radius (1737.1 km) and $g_o = \frac{GM_o}{r_o^2}$ the surface gravity. This procedure has been used since the early sixties in order to produce density models of Earth's interior assuming a starting value of density ρ_o (Alterman et al., 1959).

In order to link seismic wave velocities to density, a Birch law (Birch, 1964)
is used:

$$V_P(r) = a + b\rho(r) \tag{5}$$

where *a* and *b* are assumed to be constant because the mantle is assumed to be homogeneous. In addition, because the P-wave to S-wave velocity ratio increases with depth in previous Moon seismic models (Nakamura et al., 1982; Khan and Mosegaard, 2002; Lognonné et al., 2003; Gagnepain-Beyneix et al.,
2006), it is assumed to vary linearly with radius according to:

$$\frac{V_P(r)}{V_S(r)} = A + Br \tag{6}$$

For given values of density at the top of the mantle (= $\rho_c + 0.55$), Birch law parameters (a and b), and P to S velocity ratio parameters (A and B), a seismic model of the mantle predicting $V_P(r)$, $V_S(r)$ and $\rho(r)$ can be constructed down to the core.

For a given value of core radius (R_{core}) , and using the lunar Mass, the average core density (ρ_{core}) is deduced.

154

The procedure described above allows us to build seismic and density 155 profiles of the lunar interior obeying simple physical laws with only 6 pa-156 rameters: crust density (ρ_c) , Birch law parameters (a and b), P to S veloc-157 ity ratio parameters (A and B) inside the mantle, and core radius (R_{core}) . 158 These parameters are gathered in a model vector **m**. Average core density 159 is computed in order to fit exactly the mass of the Moon. Only models with 160 core density in the range [4.0-10.0] kg/cm³, and fitting both Love numbers 16 $k_2=0.0213\pm0.0025$ and $h_2=0.039\pm0.008$ (Williams, 2007; Goossens and Mat-162 sumoto, 2008) and polar moment of inertia ratio $IR=0.3932\pm0.0002$ (Kono-163 pliv et al., 2001) within their error bars will be selected. 164

In order to construct physical Moon models, the 6 parameters are explored 165 following ranges and steps given in table 1. The range of crustal density (ρ_c) 166 is defined according to previous estimates (Gagnepain-Beyneix et al., 2006; 167 Chenet et al., 2006). Birch law parameters are explored between values cor-168 responding to the Earth upper mantle as defined in PREM (a = -7.4146 and 169 b = 4.5872) (Dziewonski and Anderson, 1981) and IASP91 (a = -10.7346170 and b = 5.5743 (Kennett and Engdahl, 1991) reference Earth models. P 171 wave to S wave velocity ratio is explored around the value obtained for a 172 Poisson solid ($\sqrt{3} \approx 1.73$). The ranges for origin (A) and slope (B) of its 173 variation with radius are chosen in order to allow either decrease or increase 174 with depth, and variations around values obtained in previous models. Core 175 radius is explored from 250 km to 490 km. 176

 Table 1: Summary of parameter ranges explored in the construction of physical Moon

 models.

Parameter	Range	Step
Crust density (kg/cm^3) (ρ_c)	$[2.6 \ 3.0]$	-
Birch law origin (a)	[-10.74 - 7.41]	-
Birch law slope (b)	[4.58 5.57]	-
$\frac{V_P}{V_S}$ law origin (A)	$[1.0 \ 2.95]$	-
$\frac{V_P}{V_S}$ law slope (km ⁻¹) (B)	$[-0.000662 \ 0.0004]$	-
\tilde{C} ore radius (km) (R_{core})	$[250 \ 490]$	5

177 2.2. Best radial Moon models

The next step is to select the best radial Moon models that fit both P and S arrival times and geodesic observations. In order to let the core radius as a free parameter, a best radial Moon model will be obtained for each core radius.

Then, for each core radius, an exploration of the five remaining parameters 182 is performed with a Neighbourhood Algorithm (NA) (Sambridge, 1999) with 183 ten randomly selected starting models and performing twelve iterations of 184 NA with parameters ns=30 and nr=3. These parameters mean that at each 185 iteration the neighbourhoods of the three best models are explored with 10 186 new random models. The cost function to minimize is defined as the sum of 18 χ^2 functions of seismic travel times and geodesic observations (Love numbers 188 and polar moment of inertia ratio): 189

$$J(\mathbf{m}) = \frac{1}{Ns} \sum_{i}^{Ns} \frac{(t_{i}^{obs} - t_{i}^{calc})^{2}}{\sigma_{i}^{2}} + \frac{1}{3} \left(\frac{(h_{2}^{obs} - h_{2}^{calc})^{2}}{\sigma_{h_{2}}^{2}} + \frac{(k_{2}^{obs} - k_{2}^{calc})^{2}}{\sigma_{k_{2}}^{2}} + \frac{(IR^{obs} - IR^{calc})^{2}}{\sigma_{IR}^{2}} \right) (7)$$

with t_i^{obs} the observed travel time of the seismic phase (including both P and S phases), t_i^{calc} the predicted travel time inside model \mathbf{m} , σ_i^2 the travel time error, Ns the number of travel time measurements; and h_2^{obs} , h_2^{calc} , k_2^{obs} , k_2^{calc} , IR^{obs} , IR^{calc} , σ_{h_2} , σ_{k_2} and σ_{IR} respectively observed and calculated values of h_2 and k_2 Love numbers, polar moment of inertia ratio and corresponding errors. The first part of the right hand side of equation (7) will be referred to as χ^2_{seismo} , whereas the second part as χ^2_{geod} . This cost function gives an equal weight to seismological and geodetic observations in order to construct
a reference model constraining both density and seismic velocities.

The h_2^{calc} , k_2^{calc} and IR^{calc} values are computed during model construction. However, in order to be fully consistent, the computation of χ^2_{seismo} requires 199 200 relocation of all natural seismic events, and correction for P and S wave shal-20 low structure below the seismic stations. Therefore, for each physical model 202 tested, the P and S wave traveltimes given by Lognonné et al. (2003) are 203 inverted in order to relocate the events and to obtain P and S wave sta-204 tion corrections of zero average. Only arrival time data with errors smaller 205 than 10 s are kept. A total of 343 P and S travel times from 64 events (8) 206 artificial impacts, 19 meteor impacts, 10 shallow events and 27 deep moon-20 quakes) are used. The inversion is performed with a damped Gauss-Newton 208 algorithm (Tarantola, 1987) with starting event location parameters given by 209 Gagnepain-Beyneix et al. (2006) and zero station corrections. The χ^2_{seismo} 210 value of P and S wave travel times obtained after inversion is computed for 211 each physical model tested. 212

Results of the inversion are summarized in figures 2, 3 and 4. Figure 2 gives 213 an example of the parameter space sampling by NA algorithm for a core ra-214 dius of 380 km. The sampling by NA algorithm concentrates around a single 215 minimum value inside the volume of parameter space explored. Figure 3a 216 plots the minimum values of the cost function $J(\mathbf{m})$, χ^2_{geod} and χ^2_{seismo} obtained for each core radius. The best models for core radius between 300 km 217 218 and 400 km give a similar fit of the seismological and geodesic observations. 219 For core radius smaller than 300 km, the fit of seismological observations is 220 slightly degraded. For core radius larger than 400 km, χ^2_{aeod} at minimum 22 value of the cost function increases with radius, reflecting the difficulty to 222 fit geodesic observations with large core radii. Figure 3b plots the variation 223 with radius of the P and S wave velocities and density for the best mod-224 els obtained for each core radius. A comparison with the starting model of 225 Gagnepain-Beyneix et al. (2006) shows that the fit of geodesic observations 226 favours S wave velocities at the bottom of the mantle higher than previously 227 inferred. Figure 4 presents the correlation between parameters obtained for 228 the best radial models. Birch law parameters are strongly correlated be-229 tween themselves, but not with core radius. $\frac{V_P}{V_S}$ ratio presents an increase 230 with depth consistent with previous investigations. The parameters describ-231 ing the variations of $\frac{V_P}{V_S}$ ratio are correlated between themselves, but there is no significant correlation with core radius. The crust density is almost 232 233 constant around 2.76 kg/cm^3 . It means that, despite large variations of 234

Birch law parameters, imposing the average crustal thickness (40 km) and 235 the density jump at the crust/mantle interface (0.55 kg/cm^3) strongly con-236 strains the average crust density in a radial model consistent with geodesic 237 observations. However, an average crust density of 2.76 kg/cm^3 is consistent 238 with our assumptions and with previous estimates (Chenet et al., 2006). The 239 core density is correlated with core radius with high densities for small core 240 sizes and low densities for large core sizes. Overall, geodesic and travel time 24 data poorly constrain the size of the core, which motivated us to look for 242 additional constraints that could come from core reflected phases. 243

²⁴⁴ 3. Modelling core reflected phases

This section demonstrates that the core radius can be constrained by the detection of horizontaly polarized S waves reflected on the core (ScSH) and precise the data set that be can be used for such a detection. The data and signal processing methods allowing ScSH wave detections are described in the next section.

250 3.1. Waveform modelling

We focus on SH waves reflected on the core because, if the upper part 251 of the lunar core is fluid (Williams et al., 2001), their energy is completely 252 reflected back to the surface. Ray theoretical amplitudes of body waves are 253 computed including geometrical spreading and attenuation (see last table of 254 the paper for values of quality factor). As shown in figure 5a, ScSH am-255 plitude at the recording station is of the order of 10 to 20% of the direct 256 SH wave amplitude depending on the attenuation model and assuming sim-25 ilar amplitudes radiated at the source. Deep moonquakes with best signal 258 to noise ratio (mainly A01, A06 and A07 events) are assumed to be driven 259 by tides (Cheng and Toksoz, 1978; Araki, 2001). A recent analysis of the 260 focal mechanism of these events, which is based on a model that fits only 26 occurrence times of the events, suggests fault plane orientations with a dip 262 angle between 60° and 70° with large error bars (Weber et al., 2009). How-263 ever, studies of these events based only on observations of P and S wave 264 amplitudes and polarities favour focal mechanisms with a horizontal focal 265 plane (Nakamura, 1978; Koyama and Nakamura, 1980). As shown in figure 266 5b, these focal mechanisms have a maximum of SH energy radiated along 26 the vertical direction, which correspond to the take-off angles of ScSH wave. 268



Figure 2: Example of parameter space sampling by NA algorithm for a core radius of 380 km. (a) sampling projected into the plane of a and b Birch law parameters. (b) sampling projected into the plane of A and B parameters of $\frac{V_P}{V_S}$ ratio law. (c) sampling projected into the plan of α and ρ_c parameters. Each dot represents a model vector and best model values are indicated by a red star.



Figure 3: (a) Minimum values of cost function $J(\mathbf{m})$ (in red), χ^2_{geod} (in black) and χ^2_{seismo} (in blue) obtained for each core radius. Values of χ^2_{geod} (black dashed line) and χ^2_{seismo} (blue dashed line) corresponding to minimum values of the cost function $J(\mathbf{m})$ are also plotted. (b) P-wave (in red) and S-wave (in blue) velocities (in km/s), density (in green) and $\frac{V_P}{V_S}$ ratio (light blue) of the best models obtained for each core radius (dashed lines). The model of Gagnepain-Beyneix et al. (2006) is plotted as plain black lines for comparison.

In contrast, direct SH waves have a smaller excitation at the source. Conse-269 quently, for such source mechanisms, the ScSH/SH amplitude ratio is close 270 to one in the 50° - 80° epicentral distance range. Moreover, those mechanisms 271 generate SH wave and ScSH wave of opposite polarities at the source. Due 272 to the change in polarity resulting from reflection at the core surface, these 273 two body waves should thus have the same waveform. This waveform sim-274 ilarity can also be used as a posterior constraint to validate the ScSH wave 275 detection. 276

In contrast, vertically polarized S waves will lose part of their energy when reflected at the core surface due to conversion into P waves reflected and transmitted at this interface. Smaller amplitudes for ScSV waves than for ScSH waves are thus expected, as observed on Earth.

281 3.2. Error propagation

The deep moonquake records present a low signal to noise ratio. Records allowing P and S arrival detections are obtained only after stacking many individual records from the same deep moonquake cluster. Owing to this low signal to noise ratio, to the low number of stations, and to the uncertainty on the radial seismic model, the error bar on the event location coordinates are usually quite large (see table 2). In order to minimize the effect of mislocation errors and seismic structure just below the stations, ScS-S differential times



Figure 4: Correlations between parameters when considering the best radial models. (a) best values of a and b Birch law parameters. (b) best values of A and B parameters of $\frac{V_P}{V_S}$ ratio law. (c) crust and core densities as a function of core radius (in km) for the best radial models. Color scale of circles goes from black to white with increasing core radius parameter.



(b)

Figure 5: (a) ScS/S amplitude ratio without (plain line) and with (dashed line) attenuation, assuming same radiation pattern at the source; and with attenuation and radiation from an horizontal fault plane (blue line). Computations are performed in the seimic model of Gagnepain-Beyneix et al. (2006) with an S wave quality factor of 300 below 770 km depth. (b) examples of S (in red) and ScS (in blue) ray paths for a 900 km depth event. The radiation pattern (in black) of SH waves for a displacement perpendicular to the figure along an horizontal fault plane is surperimposed, with plain line for positive values, and dashed line for negative values.

are used. These differential times present a low sensitivity to the structure 289 below the station because S and ScS waves have similar crustal delays. In 290 addition, these differential times also present a low sensitivity to event mislo-291 cations along latitude and longitude coordinates, even if, as we will see below, 292 this sensitivity is non-zero. Because the largest error is on the quake depth, 293 and because this parameter is strongly influencing the ScS-S differential time 294 (hereafter called t_d), the event depth will be determined simultaneously with 295 the core radius. However, ScS-S differential times alone do not allow us to 296 relocate the lateral position of the event. Therefore, the stacking process can 297 be effective only if the errors on latitude and longitude of the events generate 298 relative ScS-S differential time variations between stations smaller than half 299 the dominant period of the records, in order to ensure coherent (in phase) 300 stack of the body waves. The differential time ScS-S at one station for an 301 event location different from the theoretical one may be written: 302

$$t_d^{j}(\theta_0 + \delta\theta, \phi_0 + \delta\phi) = t_d^{j}(\theta_0, \phi_0) + \Delta t_d + \delta t_d^{j}$$
(8)

where (θ_0, ϕ_0) are the (latitude,longitude) theoretical coordinates of the event, $\Delta t_d = \frac{1}{N} \sum_{i}^{N} \left(t_d^j(\theta_0 + \delta\theta, \phi_0 + \delta\phi) - t_d^j(\theta_0, \phi_0) \right)$ is the average differential time

shift residual over all the stations due to the event mislocation, and $\delta t_d^j =$ 305 $t_d^j(\theta_0 + \delta\theta, \phi_0 + \delta\phi) - t_d^j(\theta_0, \phi_0) - \Delta t_d$ is the differential time shift residual of 306 station j relative to this average. The second term on the right hand side 307 produces a shift of all the ScS-S differential times that is displacing the ScS 308 stack relative to its theoretical position, whereas the last term on the right 309 hand side produces relative shift between the stations that may generate 310 incoherent stacks if it is larger than half the dominant period of the body 311 wave. The relative ScS-S differential time variations between stations i and j312 is defined by $R\delta t_d^{ij} = \delta t_d^i - \delta t_d^j$. Table 2 presents an estimate of the maximum 313 values $(Max(R\delta t_d^{ij}))$ and standard deviations $(Std(R\delta t_d^{ij}))$ of relative ScS-S 314 differential time variations between stations inside the one standard devia-315 tion error ellipse of event positions. These values are controlled by the error 316 on the event location, but also by the event position relative to the stations. 317 When the back azimuth of the event is approximately the same for all the 318 stations (event outside the network area), Δt_d may be large, but $R\delta t_d^{ij}$ values 319 remain small. In contrast, for an event located in the middle of the network, 320 Δt_d is small, but $R\delta t_d^{ij}$ values present large variations. 321

Table 2: Summary of data used in this study. Parameters are the following: latitude, longitude and depth of the quake, and corresponding errors (Gagnepain-Beyneix et al., 2006), initial number of stations available, number of stations selected after removing bad quality records, parameters $Max(R\delta t_d^{ij})$ and $Std(R\delta t_d^{ij})$.

	1 0		, 1		(a /	(a /			
ſ	Event	Lat.	Long.	Depth	Δ lat.	Δ lon.	$\Delta depth$	Init.	# stat.	$Max(R\delta t_d^{ij})$	$\operatorname{Std}(R\delta t_d^{ij})$
	Name	(deg)	(deg)	(km)	(deg)	(deg)	(km)	# stat.	sel.	(s) "	(s) ^u
ľ	A01	-17,44	-38,37	917	1,1	0,6	11	4	4	1,82	1,1
	A05	-31,04	-44,92	902	3	3	80	2	2	1,34	-
	A06	49,7	54,69	860	1	0,7	11	4	4	1,57	0,9
	A07	23,97	53,7	900	0,8	0,7	12	4	4	1	0,94
	A08	-27,97	-28,08	940	2	1,2	21	1	1	-	-
	A09	-37,8	-30,85	975	4	2,6	43	3	2	8,56	-
	A10	34,01	-28,04	1139	3	3	80	2	2	0,57	-
	A11	9,6	19,49	1233	0,8	0,7	12	3	2	0,73	-
	A14	-28,7	-33,94	880	1,7	1,3	22	3	2	4,34	-
	A15	-0,94	-2,96	885	3	3	80	3	3	13,39	8,8
	A16	6,79	5,14	1105	1,2	0,7	18	3	3	2,26	1,55
	A17	23,08	-17,97	861	2,6	0,4	15	3	3	7,51	5,27
	A18	18,56	34,72	882	1,8	0,9	24	3	2	3,4	-
	A19	15,96	37,91	841	3	3	80	3	2	9,46	-
	A20	21,72	-41,01	1055	2,4	0,8	13	3	3	4,32	2,83
	A21	-15,8	-43,49	1060	3	3	80	2	1	-	-
	A24	-36,85	-38,9	980	2,1	1,7	32	4	3	4,91	2,49
	A25	34,4	59,3	898	2	1,7	26	4	4	2,57	2,1
	A26	12, 19	10,22	1135	1,5	0,7	20	3	2	1,5	-
	A27	22,51	18,53	1059	1,9	1,4	14	4	2	3,49	-
	A28	32,69	11,64	720	3	3	80	3	1	-	-
	A30	11,78	-34,26	921	1,5	1	23	4	4	1,87	2,03
	A33	6,89	117,75	887	1,5	1,3	30	3	2	0,46	-
	A34	7,04	-9,28	932	1,2	0,6	26	3	3	3,8	2,58
	A41	13,9	-26,79	953	5,6	2,2	84	3	1	-	0
	A42	22,68	-53,46	1004	1,8	1,4	24	3	2	3,94	-
I	A44	51,85	57.08	956	5.8	1.9	20	3	3	1,98	0.78

Owing to the instrument response of Apollo stations, the largest dominant period ensuring a good signal to noise ratio is about 2.5 s. Therefore, the only events for which the stacking process is expected to work properly according to the error on lateral event coordinates are events A01, A06, A07 and A44. In addition, detection by stacking process is more reliable if 4 stations are available. Consequently, only deep moonquake stacks for events A01, A06 and A07 can possibly allow ScSH reliable detections.

329 4. Data and methods

This section describes the data and method used to detect SH waves 330 reflected from the lunar core surface. First, the stacking process of individual 331 deep moonquake records along X and Y horizontal sensors is described. Then, 332 a new method, based on the energy equipartition inside the coda waves, is 333 applied to correct for relative gain variation between X and Y horizontal 334 sensors. In addition the site response below the station is corrected, and 335 data are filtered in the frequency range with highest signal to noise ratio. 336 Finally, the stacking process is described, and bootstrap validations of the 33

³³⁸ results are presented.

339 4.1. Stacks of deep moonquake individual records

Individual records of deep moonquakes are first aligned by cross-correlation 340 of the vertical component and the horizontal component with the best S/N 341 ratio. The part of the individual records presenting spikes have been removed 342 by hand from the stacks. As a result, the number of individual records stacked 343 varies with time along the stack. However this method is probably the best 344 one to ensure that no biases are introduced by a spike correction method. 345 The number of individual records stacked depends on the seismic station and 346 on the deep moonquake nest. This number is usually comprised between 20 347 and 100. An example of deep moonquake stack is presented in figure 6 which 348 shows the stacks of deep moonquake cluster A01 on the vertical component 349 of Apollo 12 station. 350

351 4.2. Correction of the gain of horizontal sensors

The horizontal components of ground velocity are recorded by two dif-352 ferent sensors (X and Y) of Apollo LP seismometers. Because these sensors 353 may have slightly different gains, the rotation of X and Y components in 354 order to reconstruct radial and transverse components may be biased. In 355 order to correct for this effect, X/Y amplitude ratios were computed for each 356 station in the coda of seismic events with high signal to noise ratios. Be-357 cause of the high level of seismic scattering in the lunar crust, the seismic 358 wavefield in the coda of lunar quakes is approximately in equipartion state 359 (Larose et al., 2005; Sens-Schönfelder and Larose, 2008). Thus, if the gains 360 of the two sensors were identical, and assuming only radial variations of seis-36 mic scattering properties, we should observe the same energy level on the 362 two horizontal components (Margerin et al., 2009), and the X/Y ratio in 363 the coda should be equal to one. If not, the X/Y ratio gives an estimate 364 of the gain ratio of the two sensors. A limitation to this analysis is a small 365 correlation between the horizontal components of the Apollo 12 seismometer 366 discovered by Vinnik et al. (2001). However, this study also indicates that 36 this correlation is not observed on the other Apollo stations. Figure 7 gives 368 an estimate of the X/Y ratio for the different stations measured in the coda 369 of different seismic events. The coda signal is defined here by the part of 370 the records starting at least 100 s after the S wave arrival. The X/Y ratio is 371 estimated by different methods (see legend of figure 7), and it presents only 372 small variations as a function of time inside the coda. For stations S12 and 373

S12Z 7.0000+00 mmmmmmmmmmmmmmmmmmmmmmmmmmmmmmm	elefter versterin for anter terier dir beite die anter ter terier ter beiter anter
\$12Z 4.5009+00 \$12Z 9.2259+00	an in the second se
S12Z 1.400e-01 S12Z 1.718e-01	in the second state of the second
812Z 1 000e-01 612Z 2 4559-01	anter and tradition for the first state of the second state
\$12Z 1.5509+01 \$12Z 2.9509+01	and a second state of the second s
\$12Z 1.7009+01	war and the second state of the second s
8122 4.500+00	eierte weren is ernete Brieferie Ber ereber Berte weret wer
8122 1.150e-01 S122 6.020e-01	en an en
\$122 4.500e+00	and the second description of the second
\$12Z 4.5009+00\$12Z 6.6249+01\$12Z 6.6249+01	an a
S12Z 7.0009-00 S12Z 7.0199-01 S12Z 7.0199-01	eler file an
\$12Z 6.0009-00 \$12Z 7.4139-01 \$12Z 7.4139-01	ale sta a serie
\$12Z 1.2009+01 \$12Z 8.0449+01 \$12Z 8.0449+01	an a
\$12Z 50009-00 \$12Z 8.5029-01 \$12Z 8.5029-01	eren an
\$122 6.000+00	ere dan mis er is spracht de statiger in general de statiger an er alle stati
S12Z 5.500+00	an the state of the
812Z 4.500e-00	and a second state the second state of the second state of the second state of the second state of the second s
\$12Z 5,5009-00 \$12Z 9,5639-01	elenter and a second and the second
\$122 4.500e-00 \$122 9.5679+01	elente anna i devete train i anna a fha anna anna anna anna anna ann
S12Z 9.7839+01S12Z 9.7839+00S12Z 9.7839+00S	elefete ale elle foreste bei alle fait i son de the Martin ale ale ale ale
\$12Z \$000e000	an a
	eletter variet i feredelik i statistik
	ele Maria a la caracterita de la c
	en ale a serie a serie de la serie de l
	and a second state of the second s
	eletterniseeriserretteinin teleteistetteiserin teleteistette
	and a second development of the second s
\$122 6.5009+00	elefter versetele der sette Beller belle Beiter ber Bertelle versetter Afrik
	elefte vereis eretike fin fin in finis i after in finis i an
	and a second the second state of the second s
	and the second descent second descent second descent second descent second descent second descent second descen
	and a second state of the
	in the second state of the
	in the second developing with a feiter i fielde an afferte
(a) Minute 0 5 10 (b) Minute 0	5 10

Figure 6: (a) examples of individual records of events belonging to deep moonquake cluster A01 and recorded on the vertical component of station Apollo 12 after alignement by cross-correlation. (b) evolution of the stack as a function of the number of records stacked. From top to bottom each line includes a new record in the stack. The numbers on the left of each trace give the maximum amplitude of the trace expressed in Apollo digital units.



Figure 7: X/Y amplitude ratios in the coda of different seismic events as a function of event origin time (in years). Event origin times after 1973 correspond to deep moonquakes. X/Y ratios are computed with different methods: time average of X/Y logarithm (filled circles), median of X/Y logarithm (crosses) and signal energy ratio (open diamonds). The average X/Y ratios are 0.856 ± 0.012 , 0.748 ± 0.010 , 0.661 ± 0.035 , 0.533 ± 0.044 respectively for seismic stations S12 (in blue), S14 (in green), S15 (in black) and S16 (in red).

S14, the codas of artificial impacts created by Lunar modules and stage IV 374 of Saturn V rocket were used because of high signal to noise ratio for these 375 events. For stations S15 and S16, deep moonquake codas with high signal 376 to noise ratios were added to artifical impacts. The X/Y ratio of different 377 events is almost constant for artificial impacts (before 1973), but it presents 378 strong variations for deep moonquakes (after 1973) possibly due to both a 379 lower signal to noise ratio and a less diffuse wavefield. However, the relative 380 gain of X and Y components can be reasonably well estimated for all the 381 stations. For stations S12 and S14, only artificial impacts are taken into ac-382 count. The Y component is then corrected for this instrumental effect before 383 performing the rotation in radial and transverse components for each deep 384 moonquake event. 385

³⁸⁶ 4.3. Correction of relative frequency responses of the stations

The horizontal component records of seismometers from the Apollo 14 and Apollo 16 missions present frequency contents significantly different from those of Apollo 12 and Apollo 15 missions. Figure 8a presents a logarithmic average of the power spectral densities of all the deep moonquake signals selected per seismic station. Apollo 14 seismic station presents an addition-



Figure 8: Logarithmic average of power spectral densities over all deep moonquake transverse records before (a) and after (b) correction of S14 and S16 transfer functions as a function of frequency for seismic stations S12 (in blue), S14 (in green), S15 (in black) and S16 (in red). On the left, curves for sensors X (dashed green) and Y (dotted green) of station S14 are also presented. All the curves have been smoothed by a moving average filter over 251 points in order to clarify the figures. Amplitude differences are due to differences of energy between the different deep moonquake records.

nal spectral peak at a frequency of 0.87 Hz, and Apollo 16 seismic station 392 presents lower energy at low frequency compared to Apollo 12 and 15 sta-393 tions. These anomalous features observed on the two horizontal sensors are 394 not present on the vertical components of the records (not shown). It sug-395 gests that this effect is mainly due to the response of the ground just below 396 the stations (site response). However, in order to be able to use the phase of 397 the records in stacks, these records must have a similar frequency content. 398 The spectral amplitudes of S14 and S16 transverse components have thus 399 been corrected by a spectral amplitude ratio computed between these sta-400 tions and an average value between stations S12 and S15. The power spectral 401 densities obtained after correction are presented in Figure 8b. These correc-402 tions of S14 and S16 records give a power spectral density similar to stations 403 S12 and S15. 404

405 4.4. Data filtering

S waves usually have more energy at lower frequencies. Moreover, we expect both the crustal scattering and the attenuation to be reduced at low frequencies. Consequently, the Apollo data recorded in peaked mode were converted into the long period mode by using theoretical responses of these two acquisition modes, and filtered by an order 3 butterworth band pass filter with corner frequencies at 0.3 Hz and 0.9 Hz. This operation allows us to



Figure 9: Logarithmic average of power spectral densities over all deep moonquake transverse records before (dotted lines) and after (plain lines) modes conversion and filtering as a function of frequency for seismic stations S12 (in blue), S14 (in green), S15 (in black) and S16 (in red). All the curves have been smoothed by a moving average filter over 251 points in order to clarify the figures.

enlarge and equalize the available frequency band. The frequency limits have
been chosen by trial and error in order to minimize the high frequency signal,
and to reduce as much as possible the lower cut off frequency. Below 0.3 Hz
and above 0.9 Hz, the noise dominates the signal in stacks of Apollo deep
moonquake data. Figure 9 presents power spectral densities of the signals
before and after the filtering process.

418 4.5. About polarisation filtering

Weber et al. (2011) used polarisation filtering in order to detect body wave arrivals reflected by deep Moon discontinuities. We evaluate the performance of this filter for picking S waves and detecting reflections from deep Moon discontinuities.

The polarisation filtering described in Weber et al. (2011) is a non linear 423 method allowing to enhance linearly polarized seismic arrivals. Assuming $\frac{V_S}{V_P}$ 424 ratio equal to 0.5 in the lunar regolith (Gagnepain-Beyneix et al., 2006), P 425 and S body waves are linearly polarized for incidence angles smaller than 426 $60^{\circ} = \sin^{-1}\left(\frac{V_S}{V_P}\right)$ Nuttli (1961). Therefore, this method can be applied to 42 most teleseismic P and SV wave arrivals on the Moon. However, assuming 428 that SH waves are present only on the transverse component, such filtering 429 is useless for these waves. 430

The radial (R) and transverse (T) components are computed from X and Y records by the following relation, assuming that X and Y sensors are aligned respectively along East and North directions (the real orientations of thesensors is given in Table 3):

$$\begin{bmatrix} R \\ T \end{bmatrix} = \begin{bmatrix} \sin\theta & \cos\theta \\ -\cos\theta & \sin\theta \end{bmatrix} \times \begin{bmatrix} X \\ Y \end{bmatrix}$$
(9)

where θ is the azimuth of the event at the receiver. In the following we will note the real (true) displacements with superscripts T and the measured displacements without superscript, and assume that $Y = Y^T$ and $X = \gamma X^T$. The gain corrections for the horizontal components has been presented above, and γ is equal to the X/Y ratio determined previously. If this correction is not applied before the rotation of X and Y components, the relations between measured radial and transverse components and the true ones is the following:

$$\begin{bmatrix} R \\ T \end{bmatrix} = \begin{bmatrix} \gamma \sin \theta & \cos \theta \\ -\gamma \cos \theta & \sin \theta \end{bmatrix} \times \begin{bmatrix} \sin \theta & -\cos \theta \\ \cos \theta & \sin \theta \end{bmatrix} \times \begin{bmatrix} R^T \\ T^T \end{bmatrix}$$
(10)

In particular, the radial component can be expressed as $R = a_{11}(\gamma)R^T + a_{12}(\gamma)T^T$ with $a_{ij}(\gamma)$ being the terms of the matrix A corresponding to the matrix product described above.

The polarisation filter (Weber et al., 2011) can be written as $OZ_j = Z_j M_j$ and $OR_j = Z_j M_j$ respectively along the vertical and radial components, with $M_j = \sum_{i=-n}^n Z_{j+i} R_{j+i}$, where j is the time step and n = 6. Now assuming that SV body wave has a motion W_j^S and an incidence angle j_o , and that ϵ_z and ϵ_r are respectively the noise on the vertical and radial component, the true vertical and radial components can be written as $Z_j^T = W_j^S \sin(j_o) + \epsilon_z$ and $R_j^T = W_j^S \cos(j_o) + \epsilon_r$. Reporting these equations in (10), and assuming $Z = Z^T$, we obtain

$$Z_{j}R_{j} = (W_{j}^{S}\sin(j_{o}) + \epsilon_{z}) \left[a_{11}(\gamma)W_{j}^{S}\cos(j_{o}) + a_{11}(\gamma)\epsilon_{r} + a_{12}(\gamma)T^{T} \right]$$
(11)

Consequently, the non linear polarisation filter is subject to two different 453 noise sources. First, the term $a_{12}(\gamma)T^T$ perturbs the radial component. Sec-454 ond, the SV wave signal should be over the noise level along the vertical 455 component $(W_j^S \sin(j_o) >> \epsilon_z)$ in order to ensure enhancement of the SV 456 wave signal. Our tests demonstrate that the first noise source due to wrong 457 rotation in the horizontal plane is generally negligible because γ is close to 458 one. Figure 10 presents the polarisation filtering performed on raw deep 459 moonquake stacks after rotation for event A01 and station S15. This figure 460

can be compared directly to figure S1 of Weber et al. (2011). SV wave signal 461 is clearly enhanced by the polarisation filtering both on OZ and OR because 462 the SV wave signal is clearly dominating noise on both vertical and radial 463 components. Such a clear enhancement of SV pulse by polarisation filtering 464 is not observed in Weber et al. (2011) study. This comparison suggests that 465 the stacks of individual deep moonquake signals coming from the same deep 466 moonquake cluster (A01 in this case) was performed differently between the 467 two studies. 468

Because the polarisation filtering is able to enhance the coherent SV wave 469 signal on both radial and vertical components, we can use this information 470 in order to refine the arrival time picks of SV waves and to infer the length 471 of the SV pulse. Figure 11 presents a focus on the polarisation filtering of 472 radial components around the SV arrival. The SV wave arrivals are clearly 473 enhanced by this process on both the raw and filtered records. More interest-474 ingly, the SV pulse length can be estimated in the 5 to 10 seconds range, and 475 it looks to be varying more with event number than with station number. 476 This observation suggests that the pulse length reflects more the properties 477 of the signal coming from the source region than the variation of scattering 478 properties below the stations. 479

However, P and S waves reflected back from discontinuities at radius smaller 480 than 500 km inside the Moon have incidence angles smaller than 2° . Ther-481 fore, the amplitude of the SV wave on the vertical component is predicted 482 to be at best 4% of the one on the radial component. Due to the high coda 483 energy and to the low signal to noise ratio of deep moonquake stacks, the SV 484 wave signal coming from deep reflectors inside the Moon will be smaller than 485 the noise on the vertical component $(W_j^S \sin(j_o) \ll \epsilon_z)$. The same argument 486 also holds for deep reflections arriving as P waves at the station. In this case, 487 the polarisation filtering will only enhance time intervals for which the noise 488 (or coda signal) is in phase on both components. 489

In conclusion, the polarisation filtering is useless for ScSH wave detection. 490 It gives good results for SV and P waves when the incidence angle is not 491 too small, and allows us to estimate the length of the S pulse in the 5-10 492 s range. However, it cannot be used for the detection of waves reflected by 493 deep discontinuities inside the Moon because in this case the noise dominates 494 the signal on one component, and both OZ and OR filtered signals present 495 enhancements for time intervals for which Z and R codas are in phase. For 496 all these reasons, we decided not to use this method for ScSH wave detection. 497



Figure 10: (top three traces): Raw deep moonquake stacks components (cluster A1) at Apollo station 15. (bottom three traces): Polarization filtered components of the same stack. S wave arrival time predicted by our best model (blue line) is presented.

Table 3: Azimuth (in degree) of Х and Υ sensors extracted Data from Apollo Scientific Experiments Handbook available at http://nssdc.gsfc.nasa.gov/planetary/online_books.html

Station	Х	Y
name	azimuth (in deg.)	azimuth (in deg.)
S12	180	270
S14	0	90
S15	0	90
S16	334.5	64.5



Figure 11: Polarisation filtering of radial components (OR_j) aligned on the hand picked SV wave arrival times for raw records (dashed lines) and records after filtering (plain lines). From top to bottom, records of stations S12, S14, S15 and S16. From left to right, records for events A01, A06 and A07. The vertical component of station S14 for event A07 is not available in our data base, consequently the polarisation filtering cannot be performed. The vertical dotted lines indicate the S wave arrival time predicted by our best moon model.



Figure 12: Results of the SH wave optimal waveform and delay times inversion. From bottom to top, optimal SH waveform (thick line) and filtered records of stations S12, S14, S15 and S16 after optimal alignment. From left to right, records for events A01, A06 and A07. Vertical dashed lines delimit the time interval with maximum coherent energy which is used below to define the optimal SH waveform.

498 4.6. S wave alignment and differential travel time computations

The arrival times of S waves on the transverse components of deep moon-499 quake stacks are hand picked by visual inspection of vertical, radial and 500 transverse components. During this process, the polarity of some records 50 has been changed in order to ensure similar polarities of S waveforms for the 502 different records of the same deep moonquake. The stacks of deep moonquake 503 records strongly depend on the S wave arrival time. In order to obtain a very 504 precise alignment of SH wave between the different stations, the records are 505 inverted by a non-linear method searching for optimal SH waveform and 506 relative delay times between the stations (Chevrot, 2002). Results of this 507 waveform matching procedure are presented in figure 12. Interestingly, the 508 best matching waveform presents significant energy on a length that is con-509 sistent with the SV pulse lengths obtained by polarisation filtering (≈ 5 s for 510 A01, ≈ 7 s for A06, ≈ 10 s for A07). The SH hand picks are corrected by 51 delays deduced from this analysis. 512

The arrival times of S and ScS waves are computed inside the best radial models for each core radius using the deep moonquake relocations obtained for these models. These computations are performed by a new implementation of the Tau-P algorithm (Buland and Chapman, 1983; Calvet and Chevrot, 2005).

518 4.7. Stacking process

All the waveforms are aligned on the S wave arrivals and normalized to maximum amplitude of the first one hundred seconds of the coda. Again,

events with less than four recording stations and events for which horizon-521 tal location errors produce relative differential times between stations larger 522 than half the dominant period ($\approx 1.25 \ s$) are excluded. Only high quality 523 events A01, A06 and A07 are kept. The stacks of the waveforms for each 524 event are performed by computing the differential times ScS-S for a given 525 moonquake depth D_i and a given core radius R_{core} using the corresponding 526 best radial model. After alignment and stack, the ScSH waveform energy 527 is computed in a 10 second window after the predicted arrival time on the 528 stacked trace. This process is repeated for all the best radial models ob-529 tained previously corresponding to core radii between 250 km and 490 km 530 with a 5 km step, and for event depth in the ± 400 km range around the 53 epicenter location with a 2 km step. Such a process allows us to compute, 532 for each event i, $NRJ_i^{ScS}(R_{core}, D_i)$ the energy of stacked ScS waveforms 533 depending on core radius R_{core} and event depth D_i . The semblance of the 534 stacked records is also defined as the ratio between the stacked ScS wave-535 form energy and the average energy of the records used to perform the stack 536 (Neidell and Taner, 1971). This parameter is varying between zero (complete 537 destructive interference) and one (fully constructive interference), providing 538 a measure of stack efficiency normalized to the energy of the records. As for 539 the energy, the semblance depends on core radius R_{core} and event depth D_i : 540 $SEMB_i^{ScS}(R_{core}, D_i)$ 54

In order to include additional a priori information on the events depth, 542 stacked energies and semblances are multiplied by a gaussian function of the 543 form $G_i(D_i) = \exp(-\frac{(D_i - D_i^0)^2}{\sigma_i^2})$ with D_i^0 the a priori event depth and ΔD_i^0 its 544 error. The standard deviation of the gaussian is defined by $\sigma_i = 10\Delta D_i^0$, in 545 order to allow large variations around the a priori event depth. A priori deep 546 moonquake locations and related errors on the parameters are extracted from 54 the study by Gagnepain-Beyneix et al. (2006). This weight function $G_i(D_i)$ 548 is only a smooth way to impose event depth in the $\pm 5\Delta D_i^0$ range around 549 theoretical value. 550

Figure 13 shows the ScSH stack energies obtained for the three events A01, A06 and A07. On these plots, a correlation between core radius and event depth is clearly seen. However, the ScSH energy presents a peak in the 380-400 km core radius range for the three events.

Once these energies are computed, their maximum value for each core radius are defined by $NRJmax_i^{ScS}(R_{core}) = \max_{D_i} [NRJ_i^{ScS}(R_{core}, D_i)]$. These functions are plotted in figure 14(a-c) for the three events selected. They



Figure 13: Stacked energies $NRJ_i^{ScS}(R_{core}, D_i)$ in color, as a function of core radius (in km) and event depth (in km), for events A01 (a), A06 (b) and A07 (c). The energies are multiplied by a gaussian function $G_i(D_i)$ centered around a priori depth D_i^0 . Color goes from blue (low energy) to red (high energy), and the maximum value is indicated by a black diamond.

present a global or local maximum in the 380-400 km core radius range. However, the statistical test performed below demonstrate that, when taken separately, the maxima of these events are statistically significant only for events A06 and A07.

To investigate the statistical significance of the results, we consider the average of maximum ScS stack energies of individual events:

$$NRJsum(R_{core}) = \frac{1}{N_{ev}} \sum_{i}^{N_{ev}} NRJmax_i^{ScS}(R_{core})$$
(12)

with N_{ev} the number of events. However, even if the records are scaled before 564 the stacking process, $NRJmax_i^{ScS}(R_{core})$ functions present different ampli-565 tudes for the different events. In our case, $NRJsum(R_{core})$ is dominated by 566 events A01 and A06. In order to give an equal weight to all the events, these 567 functions are scaled to their standard deviation and their mean is substracted 568 before summation in order to produce energy plots including all the events 569 with a similar contribution. The final result is a scaled energy depending 570 only on core radius which is defined for ScS waveform stacks by: 57

$$\overline{NRJ}sum(R_{core}) = \frac{1}{N_{ev}} \sum_{i=1}^{N_{ev}} \frac{(NRJmax_i^{ScS}(R_{core}) - \langle NRJmax_i^{ScS}(R_{core}) \rangle}{std(NRJmax_i^{ScS}(R_{core}))}$$
(13)

with \ll and std() respectively the average and standard deviation operators. 572 The same operations are performed for the semblance by computing for each 573 event the maximum semblance at different core radius $(SEMBmax_i^{ScS}(R_{core}))$ 574 and the average of these curves over all the events $(SEMBsum(R_{core}))$. The 575 scaled version of semblance curve does not have to be computed because 576 the semblance measure is already normalized to the energy of the records. 577 Functions $NRJsum(R_{core})$, $\overline{NRJ}sum(R_{core})$ and $SEMBsum(R_{core})$ are pre-578 sented in panels (d), (e) and (f) of figure 14. This figure demonstrates that 579 when the three events are taken together the energy maximas at 380 and 580 395 km core radius are statistically significant (at three standard deviations 581 level). 582

In order to test the dependence of the results on the filtering process, the whole process (including S wave alignment) is repeated on the data before acquisition mode conversion and bandpass filtering. The results are presented in panels (g), (h) and (i) of figure 14. The peaks of ScSH wave energy around 380 and 395 km core radius are also present but less statistically significant. The consistency of the results between the two different frequency ranges strongly argue in favour of a ScSH detection. Moreover, the lower ScSH energy at high frequencies (in peaked mode) than at low frequencies (in long period bandpass mode) justifies the search for this body wave at frequencies as low as possible.

Because the ScSH wave stacks may be slightly shifted inside the ten seconds 593 time window, the core radius obtained may be also shifted. For example, 594 if the energy of ScSH wave stack inside the window is significant only 2 or 595 3 s after the beginning of the window, S-ScS travel time is under-estimated 596 and core radius over-estimated. In order to remove this effect, the records 597 obtained after filtering have been deconvoled from the optimal source time 598 functions presented on figure 12. After deconvolution, SH energy is focused 599 on a 2 s window. The stacking process is reproduced by computing energy on 600 a 2 s window centered on the ScS arrival. The results are presented in figure 601 15, for the three different moonquakes. Clear maximum of ScSH energy are 602 obtained for events A06 and A07, but at slightly smaller core radius (370-390) 603 km), which suggests that the over-estimation of the core radius due to the 604 10 s window may be real. However, the small size of stacking window has 605 the drawback to focus the stack energy in a very narrow core radius range. 606 Due to quake mislocations and also possibly to lateral heterogeneities at the 607 base of the lunar mantle, the real ScS-S differential travel times vary from 608 one event to the other and different core radius are obtained for the different 609 events. As a consequence, the three curves do not interfere constructively 610 when summed together. 611

The test presented above and the increasing difficulty to explain geodesic observations with increasing core radius above 380 km, favour a core radius value at the lowest range of the broad energy peak observed on figure 14. Optimal core radius estimate is 380 km, with a 30 km error bar estimated from the range of core radius for which the energy is above the two standard deviation level.

A similar exercise is also done for the radial components of the records in order to detect ScSV waves. The results obtained on filtered data are presented on figure 16. As expected, ScSV wave is not detected inside the S coda because its amplitude is smaller than ScSH one. This exercise also demonstrates that the bootstrap method described below is pertinent for the validation of ScSH detections.



Figure 14: Plots of stacked maximum energies $NRJmax_i(R_{core})$ for events A01 (a), A06 (b), A07 (c), and the average of these energies $NRJsum(R_{core})$ (d), the scaled average of these energies $\overline{NRJsum}(R_{core})$ (e) (red curves), and the average semblance $SEMBsum(R_{core})$ (f) (red curve). Panels (g), (h) and (i) are identical respectively to panels (d), (e) and (f), but for data before acquisition mode conversion and bandpass filtering. The average value (blue plain line), the one standard deviation around this value (blue dashed lines) and the two standard deviation value (blue dot-dashed line) obtained for the bootstrap ensemble are shown on each plot. On panels (d), (e), (f), (g), (h) and (i) curves for individual events (thin black lines) are also presented.



Figure 15: Plots of stacked maximum energies $NRJmax_i(R_{core})$ after deconvolution of optimal SH waveforms for events A01 (a), A06 (b), A07 (c). The average value (blue plain line), the one standard deviation around this value (blue dashed lines) and the two standard deviation value (blue dot-dashed line) obtained for the bootstrap ensemble are shown on each plot.



Figure 16: Plots of $NRJsum(R_{core})$ (a), $\overline{NRJsum(R_{core})}$ (b) and $SEMBsum(R_{core})$ (c) (red curves) for stacks of the radial components of the records. The average value (blue plain line), the one standard deviation around this value (blue dashed lines) and the two standard deviation value (blue dot-dashed line) obtained for the bootstrap ensemble are shown. Curves obtained for individual events (thin black lines) are also presented.

624 4.8. Validation of the results with bootstrap

We applied a bootstrap method to test the statistical significance of our 625 results (Efron and Tibshirani, 1993). The SH arrival picks are perturbed 626 randomly in a ± 30 s range. We repeat the stacking process for each new 627 data set. We then compute the mean, maximum and standard deviation 628 over 150 random realizations of the resulting stacks of energy. This method 629 gives an estimate of the background noise corresponding to random waveform 630 alignment. A peak can be considered significant if it is above two standard 631 deviations of the bootstrap ensemble. 632

As described previously, the two standard deviation level is passed in the 380-400 km core radius range for filtered data using a 10s window (Figure 14), and in the 370-390 km core radius range after deconvolution of optimal SH waveforms for events A06 and A07. The statistical validation is obtained for ScSH detection and not for ScSV detection. Moreover, an error estimate of ± 40 km is provided. This error will be evaluated more precisely below.

639 4.9. Stacked waveforms comparison

Figure 17 presents record sections of transverse components aligned on 640 predicted ScSH arrival for a 380 km core radius. After alignment on ScSH, 641 the waveforms are stacked in order to produce a ScSH stacked waveform for 642 each event. Similar processing is also done for the SH wave. The comparison 643 of these stacked waveforms is shown in figure 18. In this figure, the SH 644 and ScSH waveforms have been cross-correlated on a 10 s window, and are 645 presented for the best correlation within a ± 2 s time shift of ScSH stack. 646 This shift correspond to the value of Δt_d due to the error on the (longitude, 64 latitude) coordinates of the quake, and it should be below 2 s for the events 648 processed in this study. A good correlation between ScSH and SH stacks is 640 obtained for events A06 and A07, but it is low for event A01. This waveform 650 similarity, already enhanced by the success of stacking after deconvolution of 651 SH optimal waveform, gives further support for a ScSH detection. 652

653 5. Discussion

654 5.1. Error estimates

Figure 14 provides a formal error estimate on the core radius which takes into account the uncertainty in the stacking process, and errors on the depth of the events. However, the error on the seismic model must also be taken



Figure 17: Record sections of transverse components plotted as a function of epicentral distance (in degrees) and time relative to predicted ScSH arrival time for a 365 km core radius (in seconds). Red marker indicate the SH wave arrival time pick. Vertical dashed lines indicate the 10 second window used to stack ScSH waveforms. Different colors are used for the different quakes: A01 in black, A06 in blue and A07 in green.

into account in order to estimate its effect on the core radius. From the set 658 of models generated by the NA algorithm at 380 km radius, we compute the 659 maximum and minimum values of seismic velocities and densities at each 660 depth inside the ensemble of models within the half width of the probability 661 peak. These values define the error bars on the best radial model. They 662 are plotted on figure 19a. These error bars are almost constant inside the 663 mantle for density and P-wave velocity with a relative error of respectively 664 0.2% and 3.3%. However, the error on S-wave velocity presents a minimum in 665 the mid-mantle (3%) and a maximum (11%) at the base of the mantle. The 666 strong increase in S-wave velocity errors at the base of the mantle translates 667 to a significant error on the absolute value of core radius. Considering a 668 vertically incident ScS wave from a deep moonquake at a depth of 900 km, 660 the integrated error on the S-wave velocity profile below the event produces 670 an error on the ScS travel time of about 9% on the two-way travel time from 671 the event to the core, or about 19 s. This travel time error can be translated 672 directly into an error on the core radius of approximately 33 km. This rough 673 estimate is probably an upper estimate because the vertical incidence of ScS 674 rays has the highest sensitivity to core radius. However, it highlights the 675



Figure 18: Comparison between SH (black plain line) and ScSH (blue dashed line) stacks as a function of time and event number. The ScS stacks are aligned for best correlation in the ± 2 seconds range. Blue diamonds indicate the start of ScS stack window before alignment. Events numbers are 1 for A01, 2 for A06 and 3 for A07. Correlation coefficient over the 10 seconds window is indicated along the stack before the stack window.

difficulty to obtain an absolute value of core radius without S-wave arrival time measurements at large epicentral distances. Taking into account the true ray geometries, and the bootstrap analysis of ScSH wave detection, the error bar on the core radius is about 40 km.

The error on the average core density for a 380 km core radius is about 0.3680 kg/cm³. By looking at figure 4c, varying the core radius in a range of ± 40 681 km around its best estimate gives approximately two times larger average 682 core density variation than the error bar estimate at 380 km core radius. 683 Moreover, because the core density is inferred from mass and moment of 684 inertia, and due to the low value of the core moment of inertia (of the same 685 order as the error bar on the moment of inertia of the whole planet), small 686 variations of crustal thickness and density may generate large variations of 68 core density. The average crustal thickness is not inverted here, but the 688 error on this parameter requires to increase our estimate of the error on the 689 core density. Consequently, a conservative estimate of average core density 690 is $5.2 \pm 1.0 \text{ kg/cm}^3$. 691

⁶⁹² 5.2. Comparison with previous results

Our estimates of core radius at 380 ± 40 km and average core density at 693 5.2 ± 1.0 kg/cm³ are respectively at the upper and lower limits of previous 694 estimates from both lunar laser ranging observations (Williams et al., 2001) 695 and induced magnetic moment of the Moon (Hood et al., 1999). This seis-696 mic estimate of core radius is significantly larger than the 330 km proposed 697 by Weber et al. (2011), which in some way indicates a large sensitivity to 698 uncertainties in the seismic model at the base of the mantle and to error 699 propagation. However their large error bars of these core radius estimates 700 cover the domain of previously inferred values. Moreover, the detection of 701 ScSH waves and not ScSV waves supports a liquid core beneath the core 702 mantle boundary, as already suggested by the dissipation of lunar rotation 703 (Williams et al., 2001). The average core density is relatively low and sug-704 gests either a high level of light elements in a completely fluid core, or a large 705 core temperature. For example, if the average core density is explained by 706 the presence of sulfur alone, more than 10% are required for the nominal 707 value (Sanloup et al., 2000; Balog et al., 2003). But, when the error bar is 708 taken into account the percent of sulfur content can vary from almost zero to 709 large values. However, because an inner core is expected for thermodynam-710 ical reasons (Wieczorek et al., 2006) and its size is not constrained by this 711

study, the interpretation of the average core density into core composition isstrongly limited.

714 6. Description of the best model

This section gives seismic event location parameters, station corrections, 715 and the reference model. The reference model is denominated VPREMOON 716 for Very Preliminary REference MOON model. The parameter values, and 717 related error bars at fixed core radius, for this model are: $\rho_c = 2.762 \pm 0.0048$, 718 719 $-0.000054 \pm 0.000251 km^{-1}$ and $R_{core} = 380 \ km$. In this model, calcu-720 lated values of geodesic observations are $k_2^{calc} = 0.0223, h_2^{calc} = 0.0394,$ 72 $IR^{calc} = 0.3932$ and $l_2^{calc} = 0.0106$ (this last parameter is not inverted here). 722 The values obtained at best fit are $\chi^2_{seismo} = 1.4814$ and $\chi^2_{geod} = 0.0575$. For 723 comparison, our starting model derived from Gagnepain-Beyneix et al. (2006) 724 model gives $k_2^{calc} = 0.0231, h_2^{calc} = 0.0408, IR^{calc} = 0.3931, l_2^{calc} = 0.0110,$ 725 $\chi^2_{seismo} = 6.232$ and $\chi^2_{geod} = 0.301$. 726

Table 4 provides the relocations of the events used in this study inside the 727 VPREMOON model. These locations are close to the locations published by 728 Gagnepain-Beyneix et al. (2006) because the seismic model is very similar in 729 most of the mantle. The errors on these locations are underestimated, be-730 cause the uncertainty on the velocity model is not formally taken into account 73 in their computation. Table 5 gives station corrections. These corrections 732 are small and their relative error is large. Table 6 and figure 19 present the 733 VPREMOON model. The model is separated in a seismic model in which 734 the crustal thickness (28 km) is compatible with near side crustal structure 735 below the Apollo network, and a geodesic model in which the Moho depth 736 is corrected to its average value over the whole planet (40 km). P wave ve-737 locity inside the core is not constrained by our study. Assuming that the 738 average core density is similar to the density of the liquid core, high pres-739 sure experiments suggest a P wave velocity close to 4.3 km/s at these pres-740 sure/temperature conditions (Sanloup et al., 2004). However, this value is 741 not used in our model because the core internal structure is not constrained. 742 P and S wave attenuations are taken from studies by Nakamura and Koyama 743 (1982); Nakamura et al. (1982), and arbitrarily fixed in the deep mantle. 744

Event	lat. (θ)	long. (ϕ)	depth (z)	σ_{θ}	σ_{ϕ}	σ_z	origin	origin time	σ_{to}
name	(in [°])	(in [°])	(in km)	(in [°])	(in ^{'o})	(in km)	date	(in s)	(in s)
12LM	-3.94	-21.20	0.0	0.00	0.00	0.0	6911202217	17.70	0.00
13S4	-2.75	-27.86	0.0	0.00	0.00	0.0	7004150209	41.00	0.00
14S4	-8.09	-26.02	0.0	0.00	0.00	0.0	7102040740	55.40	0.00
14LM	-3.42	-19.67	0.0	0.00	0.00	0.0	7102070045	25.70	0.00
15S4	-1.51	-11.81	0.0	0.00	0.00	0.0	7107292058	42.90	0.00
15LM	26.36	0.25	0.0	0.00	0.00	0.0	7108030303	37.00	0.00
16S4	1.30	-23.80	0.0	0.00	0.00	0.0	7204192102	4.00	0.00
17S4	-4.21	-12.31	0.0	0.00	0.00	0.0	7212102032	42.30	0.00
M1	73.52	2.79	0.0	0.64	2.77	0.0	7201040631	19.80	2.48
M2	1.55	-16.91	0.0	0.19	0.19	0.0	7205130846	39.04	0.56
M3	33.02	137.22	0.0	0.93	1.02	0.0	7207172150	56.66	1 29
M4	23.92	10.08	0.0	0.27	0.52	0.0	7207311808	15 23	1.68
M5	15.69	22.44	0.0	1.35	1 21	0.0	7208292258	33.50	2.85
M6	28.85	40.68	0.0	2 51	1 12	0.0	7309262046	16 32	2.88
M7	-24.60	-24.87	0.0	1.00	1.94	0.0	7312241003	19.38	2.00
M8	7 45	22 29	0.0	0.65	0.00	0.0	7404191830	3 11	2.55
MO	20.22	-55.52	0.0	0.05	0.50	0.0	7404131030	2.54	1.57
M10	20.23	10.40	0.0	0.41	0.03	0.0	7407171203	40.51	2.45
M11	-1.20	19.10	0.0	0.85	0.72	0.0	7411211313	40.51	1.74
M10	1.08	-0.10	0.0	0.87	0.39	0.0	7412130907	10.10	1.74
N112	-31.80	4.10	0.0	1.22	2.37	0.0	7505052149	22.20	2.92
M13	2.43	43.31	0.0	0.52	0.97	0.0	7504121812	38.22	2.92
M14	-37.10	-121.04	0.0	1.45	1.20	0.0	7505040959	28.51	2.34
M15	-39.24	62.77	0.0	1.79	1.46	0.0	7601130711	22.96	2.63
M16	-16.62	-9.87	0.0	0.96	0.68	0.0	7605280601	56.29	2.44
M17	23.69	-73.88	0.0	1.02	0.99	0.0	7611142313	6.60	2.38
M18	-20.39	-64.47	0.0	0.72	0.94	0.0	7704172332	6.87	2.44
M19	-13.06	-74.91	0.0	5.66	1.23	0.0	7706282222	31.15	2.86
SH1	12.78	50.78	15.9	1.42	2.69	68.6	7209171435	2.96	7.31
SH2	47.79	38.06	8.8	3.14	3.32	37.5	7212062308	33.52	8.23
SH3	-84.71	-137.13	71.3	0.85	1.48	38.6	7303130756	23.63	4.35
SH4	22.35	82.93	0.0	1.66	2.34	7.6	7407110046	19.16	6.53
SH5	26.32	-92.28	0.0	1.58	2.40	6.3	7501030141	56.19	5.10
SH6	65.81	58.96	20.3	1.02	1.13	13.3	7501120313	48.28	4.58
SH7	-16.93	-25.84	127.6	1.62	1.95	85.1	7502132203	50.43	6.68
SH8	44.15	33.94	168.1	2.31	1.84	94.4	7601041118	55.38	6.72
SH9	52.30	-25.83	136.3	0.77	1.08	37.3	7603061012	23.38	2.77
SH10	-18.71	-12.92	79.3	1.13	1.21	80.7	7603081442	10.63	5.28
A01	-17.31	-38.21	918.5	0.58	0.87	8.0	7309300410	58.29	1.40
A06	49.68	54.65	861.2	0.76	0.75	8.1	7607021052	23.70	1.16
A07	23.98	53.64	901.0	0.64	0.62	8.9	7607020311	22.88	1.18
A08	-27.99	-28.03	939.9	1.61	1.34	18.4	7705161052	28.80	3.00
A09	-37.71	-30.71	974.5	2.21	3.30	33.8	7704161958	3.76	4.89
A11	9.29	17.47	1200.4	0.68	0.76	10.3	7706180501	15.12	2.03
A14	-28.65	-33.80	880.6	1.22	1.32	15.8	7305281853	12.49	3.13
A16	6.83	5.07	1104.2	0.63	0.91	13.4	7210081524	35.05	2.04
A17	23.09	-18.00	861.1	1.20	1.32	13.3	7211070852	7.86	2.14
A18	18.56	34.66	882.1	1.39	0.92	18.6	7301052250	29.71	2.17
A20	21.72	-40.88	1055.3	0.63	1.83	10.5	7205151718	6.50	2.58
A24	-36.76	-38.81	980.1	1 79	1.68	26.2	7706121817	37.99	3.62
A 25	34 33	59.23	899.3	1.52	1.35	19.4	7706092015	6 64	2 32
A 26	12 14	10.13	1135.0	0.88	1.03	16.7	7706201450	48.48	3.08
A20	22.14	18 47	1058.7	1.20	1.05	11.0	7705160001	51 19	1.92
A 30	22.40	34.91	021 /	1.29	1.00	16.5	7205170042	45.25	2.37
A30	6.01	-34.21	921.4	1.00	1.09	21.5	7203170042	40.00	2.37
A33 A24	7.04	0.20	000.1	1.05	1.10	21.0 19.9	7206141933	44.95	2.31
A34 A40	1.60	-9.29	931.4	0.00	0.62	10.0	7206070240	20.91	2.09
A40	-1.00	-10.93	880.4	0.88	0.62	17.0	7306081616	35.15	3.00
A41	13.88	-20.04	951.8	2.43	3.31	48.1	7205081616	24.00	1.43
A42	22.69	-53.38	1004.6	1.37	1.32	17.2	7305030152	34.84	2.44
A44	51.51	56.86	956.8	4.06	2.42	14.6	7405190309	3.63	3.71
A50	9.41	-51.45	835.5	1.23	1.63	21.5	7304300105	25.53	4.69
A51	8.85	15.75	887.1	0.55	0.83	18.4	7402180835	27.18	3.41
A84	-10.03	-31.76	862.2	1.97	2.43	17.3	7607221946	28.41	4.56
A85	27.90	59.16	801.7	1.38	2.87	20.2	7707191037	50.84	8.21
A97	-3.39	18.66	999.9	1.74	2.06	18.9	7705190608	21.00	3.51

Table 4: Location parameters of the event used in the study inside the VPREMOON model.

Station	P cor.	P cor.	S cor.	S cor.
name	(in s)	error $(in s)$	(in s)	error (in s)
S12	-1.034	0.250	-0.229	0.462
S14	1.162	0.230	-0.584	0.413
S15	-0.298	0.279	-0.950	0.468
S16	0.171	0.758	1.763	1.344

Table 5: P and S wave station corrections and associated error bars.



Figure 19: VPREMOON seismological (a) and geodesic models (b). On the left (a), P and S wave velocities (in km/s) and density (in kg/cm^3) are plotted as a function of radius (in km) for the seismological model. The error bars are indicated for each parameters by dot-dashed lines. On the right (b), Pressure (in GPa), gravity (in 0.1m/s^2) and density (in kg/cm^3) are plotted as a function of radius (in km) for the geodesic model.

Table 6: VPREMOON model: on the left the seismic model and on the right the geodesic model in which Moho depth as been corrected to 40 km. Attenuation parameters are extracted from previous studies (Nakamura and Koyama, 1982; Nakamura et al., 1982) and arbitrarily fixed in the deep mantle. Seismic velocities and attenuation parameters inside the core are arbitrarily fixed by the authors.

radius	V_P	V_S	density	Q_P	Q_S	radius	density	gravity	pressure
(in km)	(in km/s)	(in km/s)	$(in kg/cm^3)$			(in km)	$(in kg/cm^3)$	(m/s^2)	(in GPa)
1737.1	1.00	0.50	2.600	6750.0	6750.0	1737.1	2.600	1.6248	0.0000
1736.1	1.00	0.50	2.600	6750.0	6750.0	1736.1	2.600	1.6245	0.0056
1736.1	3.20	1.80	2.762	6750.0	6750.0	1736.1	2.762	1.6245	0.0056
1725.1	3.20	1.80	2.762	6750.0	6750.0	1725.1	2.762	1.6196	0.0781
1725.1	5.50	3.30	2.762	6750.0	6750.0	1725.1	2.762	1.6196	0.0781
1709.1	5.50	3.30	2.762	6750.0	6750.0	1709.1	2.762	1.6127	0.1825
1709.1	7.54	4.34	3.312	6750.0	6750.0	1697.1	2.762	1.6076	0.2599
1697.1	7.55	4.34	3.314	6750.0	6750.0	1697.1	3.314	1.6076	0.2599
1671.7	7.57	4.35	3.318	9000.0	4000.0	1671.7	3.318	1.5851	0.5086
1647.1	7.59	4.36	3.322	9000.0	4000.0	1647.1	3.322	1.5632	0.7470
1627.1	7.61	4.37	3.325	9000.0	4000.0	1627.1	3.325	1.5454	0.9389
1607.1	7.63	4.38	3.329	9000.0	4000.0	1607.1	3.329	1.5276	1.1290
1587.1	7.64	4.39	3.332	9000.0	4000.0	1587.1	3.332	1.5098	1.3174
1567.1	7.66	4.40	3.335	9000.0	4000.0	1567.1	3.335	1.4920	1.5040
1547.1	7.68	4.40	3.338	9000.0	4000.0	1547.1	3.338	1.4741	1.6888
1527.1	7.69	4.41	3.341	9000.0	4000.0	1527.1	3.341	1.4562	1.8718
1502.0	7.71	4.42	3.344	9000.0	4000.0	1502.0	3.344	1.4338	2.0988
1487.1	7.72	4.43	3.346	9000.0	4000.0	1487.1	3.346	1.4204	2.2321
1461.7	7.74	4.44	3.350	3375.0	1500.0	1461.7	3.350	1.3976	2.4570
1447.1	7.75	4.44	3.352	3375.0	1500.0	1447.1	3.352	1.3845	2.5848
1427.1	7.77	4.45	3.355	3375.0	1500.0	1427.1	3.355	1.3666	2.7583
1407.1	7.78	4.45	3.357	3375.0	1500.0	1407.1	3.357	1.3486	2.9297
1387.1	7.80	4.46	3.360	3375.0	1500.0	1387.1	3.360	1.3306	3.0992
1367.1	7.81	4.47	3.363	3375.0	1500.0	1367.1	3.363	1.3126	3.2666
1347.1	7.82	4.47	3.365	3375.0	1500.0	1347.1	3.365	1.2946	3.4320
1327.1	7.84	4.48	3.368	3375.0	1500.0	1327.1	3.368	1.2766	3.5954
1307.1	7.85	4.49	3.370	3375.0	1500.0	1307.1	3.370	1.2586	3.7566
1287.1	7.86	4.49	3.373	3375.0	1500.0	1287.1	3.373	1.2405	3.9157
1267.1	7.88	4.50	3.375	3375.0	1500.0	1267.1	3.375	1.2225	4.0728
1252.0	7.88	4.50	3.377	3375.0	1500.0	1252.0	3.377	1.2089	4.1899
1231.7	7.90	4.51	3.379	1125.0	500.0	1231.7	3.379	1.1906	4.3454
1207.1	7.91	4.51	3.382	1125.0	500.0	1207.1	3.382	1.1685	4.5308
1187.1	7.92	4.52	3.384	1125.0	500.0	1187.1	3.384	1.1505	4.6791
1167.1	7.94	4.53	3.386	1125.0	500.0	1167.1	3.386	1.1325	4.8252
1147.1	7.95	4.53	3.388	1125.0	500.0	1147.1	3.388	1.1145	4.9690
1127.1	7.96	4.54	3.391	1125.0	500.0	1127.1	3.391	1.0965	5.1106
1107.1	7.97	4.54	3.393	1125.0	500.0	1107.1	3.393	1.0786	5.2499
1087.1	7.98	4.54	3.395	1125.0	500.0	1087.1	3.395	1.0606	5.3869
1067.1	7.99	4.55	3.397	1125.0	500.0	1067.1	3.397	1.0427	5.5215
1047.1	8.00	4.55	3.398	1125.0	500.0	1047.1	3.398	1.0249	5.6539
1027.1	8.01	4.56	3.400	1125.0	500.0	1027.1	3.400	1.0070	5.7838
1002.0	8.02	4.56	3.403	1125.0	500.0	1002.0	3.403	0.9847	5.9436
987.1	8.03	4.57	3.404	1125.0	500.0	987.1	3.404	0.9715	6.0367
961.7	8.04	4.57	3.406	675.0	300.0	961.7	3.406	0.9490	6.1922
947.1	8.05	4.57	3.408	675.0	300.0	947.1	3.408	0.9361	6.2798
927.1	8.06	4.58	3.409	675.0	300.0	927.1	3.409	0.9185	6.3977
907.1	8.07	4.58	3.411	675.0	300.0	907.1	3.411	0.9010	6.5132
887.1	8.08	4.58	3.413	675.0	300.0	887.1	3.413	0.8835	6.6262
867.1	8.08	4.59	3.414	675.0	300.0	867.1	3.414	0.8662	6.7367
847.1	8.09	4.59	3.416	675.0	300.0	847.1	3.416	0.8489	6.8446
827.1	8.10	4.59	3.417	675.0	300.0	827.1	3.417	0.8318	6.9500
807.1	8.11	4.60	3.419	675.0	300.0	807.1	3.419	0.8147	7.0529
787.1	8.12	4.60	3.420	675.0	300.0	787.1	3.420	0.7978	7.1531
767.1	8.12	4.60	3.421	675.0	300.0	767.1	3.421	0.7811	7.2508
747.1	8.13	4.61	3.423	675.0	300.0	747.1	3.423	0.7645	7.3458
727.1	8.14	4.61	3.424	675.0	300.0	727.1	3.424	0.7481	7.4382
707.1	8.14	4.61	3.425	675.0	300.0	707.1	3.425	0.7320	7.5280
687.1	8.15	4.61	3.427	675.0	300.0	687.1	3.427	0.7160	7.6150
667.1	8.16	4.62	3.428	675.0	300.0	667.1	3.428	0.7004	7.6992
647.1	8.16	4.62	3.429	675.0	300.0	647.1	3.429	0.6850	7.7808
627.1	8.17	4.62	3.430	675.0	300.0	627.1	3.430	0.6700	7.8595
607.1	8.18	4.62	3.431	675.0	300.0	607.1	3.431	0.6554	7.9354
587.1	8.18	4.62	3.433	675.0	300.0	587.1	3.433	0.6413	8.0085
567.1	8.19	4.63	3.434	675.0	300.0	567.1	3.434	0.6277	8.0786
547.1	8.19	4.63	3.435	675.0	300.0	547.1	3.435	0.6147	8.1458
527.1	8.20	4.63	3.436	675.0	300.0	527.1	3.436	0.6024	8.2100
507.1	8.20	4.63	3.437	675.0	300.0	507.1	3.437	0.5909	8.2711
487.1	8.21	4.63	3.438	675.0	300.0	487.1	3.438	0.5804	8.3291
467.1	8.21	4.63	3.438	675.0	300.0	467.1	3.438	0.5710	8.3839
447.1	8.22	4.63	3.439	675 A	300.0	447.1	3.439	0.5629	8.4353
427.1	8.22	4.64	3.440	67 9 9	300.0	427.1	3.440	0.5564	8.4834
407.1	8.23	4.64	3.441	675.0	300.0	407.1	3.441	0.5518	8.5279
387.1	8.23	4.64	3.442	675.0	300.0	387.1	3.442	0.5495	8.5687
380.0	8.23	4.64	3.442	675.0	300.0	380.0	3.442	0.5494	8.5823
380.0	?	?	5.171	10000.0	10000.0	380.0	5.171	0.5494	8.5823
360.0	?	?	5.171	10000.0	10000.0	360.0	5.171	0.5205	8.6929
340.0	?	?	5.171	10000.0	10000.0	340.0	5.171	0.4915	8.7976
320.0	?	?	5.171	10000.0	10000.0	320.0	5.171	0.4626	8.8963
300.0	?	?	5.171	10000.0	10000.0	300.0	5.171	0.4337	8.9890
280.0	?	?	5.171	10000.0	10000.0	280.0	5.171	0.4048	9.0757
260.0	?	?	5.171	10000.0	10000.0	260.0	5.171	0.3759	9.1565
240.0	?	?	5.171	10000.0	10000.0	240.0	5.171	0.3470	9.2312
220.0	?	?	5.171	10000.0	10000.0	220.0	5.171	0.3181	9.3000
200.0	?	?	5.171	10000.0	10000.0	200.0	5.171	0.2891	9.3628
180.0	?	?	5.171	10000.0	10000.0	180.0	5.171	0.2602	9.4196
160.0	?	?	5.171	10000.0	10000.0	160.0	5.171	0.2313	9.4705
140.0	?	?	5.171	10000.0	10000.0	140.0	5.171	0.2024	9.5153
120.0	?	?	5.171	10000.0	10000.0	120.0	5.171	0.1735	9.5542
100.0	?	?	5.171	10000.0	10000.0	100.0	5.171	0.1446	9.5871
80.0	?	?	5.171	10000.0	10000.0	80.0	5.171	0.1157	9.6140
60.0	?	?	5.171	10000.0	10000.0	60.0	5.171	0.0867	9.6349

745 7. Conclusion

We have constructed a preliminary reference model of the Moon based on 746 a priori crustal structure, physical constraints on density and seismic veloc-747 ities variations with depth, by fitting both seismological and geodesic data. 748 The core radius is determined from the detection of transversely polarized 749 core reflected S wave from a low number of deep moonquakes properly lo-750 cated and presenting high signal to noise ratio. The VPREMOON model 751 constrains the core size to 380 ± 40 km radius and average density to 5.2 ± 1.0 752 kg/cm^3 , and favours a liquid outer core. It constitutes the first reference 753 model including simultaneously physical constraints, geodesic and seismo-754 logical observations, and detection of S waves reflected on the lunar core. 755 However, the internal structure of the lunar core remains largely unknown, 756 and the model is still characterized by rather strong uncertainties on the 757 different parameters owing to the paucity of available data. 758

The constraints on the core density are strongly related to geodesic parame-759 ters such as the polar moment of inertia of the Moon, but also to the average 760 crustal structure. The average crustal thickness is fixed in our model, but 761 its variation can change significantly the polar moment of inertia budget of 762 the planet, and consequently the core density obtained. Further constraints 763 brought by SELENE and GRAIL missions on these parameters will indirectly 764 strongly constrain the average core density, and the radius of the inner core 765 which is expected for thermodynamical reasons (Wieczorek et al., 2006), and 766 for which a seismic signature has been suggested by Weber et al. (2011). 76 Our model relies on the hypotheses of homogeneity and adiabaticity of the 768 lunar mantle. Consequently, radial and lateral deviations from this model, 769 that may eventually be detected by future lunar seismometers, will provide 770 additional constraints on the internal dynamics of the lunar interior. In par-771 ticular, a high temperature gradient or partial melt inside the upper and 772 lower boundary layers of the mantle may strongly modify seismic velocities 773 and density in these regions. Both the very broad band planetary seismome-774 ters developed in the last decades (Lognonné et al., 1996, 2000; Lognonné, 775 2005) and future lunar geophysical stations, such as SELENE2 (Tanaka et al., 776 2008) and Lunette/ILN (Neal et al., 2010) will provide crucial additional data 77 to further improve our knowledge of the lunar interior. 778

779 8. acknowledgments

We acknowledge Vadim Monteiller for helpful discussions concerning quake relocation methods. This study was supported by Centre National d'Etudes Spatiales (CNES) research projects, Programme National de Planétologie (PNP) of CNRS-INSU, PRES "Université de Toulouse" (Toulouse University) and Campus Spatial Paris Diderot (IPGP contribution number XXX). We thank the two anonymous reviewers for improving the paper by their constructive comments.

787 References

- ⁷⁸⁸ Alterman, Z., Jarosch, H., Pekeris, C. L., Aug. 1959. Oscillations of the
 ⁷⁸⁹ Earth. Royal Society of London Proceedings Series A 252, 80–95.
- Araki, H., 2001. Focal processes of deep moonquakes. J. Geod. Soc. Japan
 47, 508–513.
- Balog, P. S., Secco, R. A., Rubie, D. C., Frost, D. J., Feb. 2003. Equation of
 state of liquid Fe-10 wt % S: Implications for the metallic cores of planetary
 bodies. Journal of Geophysical Research (Solid Earth) 108, 2124-+.
- Benz, W., Cameron, A. G. W., Melosh, H. J., Sep. 1989. The origin of the
 moon and the single impact hypothesis. III. Icarus 81, 113–131.
- Bina, C. R., Dec. 2003. Seismological Constraints upon Mantle Composition.
 Treatise on Geochemistry 2, 39–59.
- Birch, F., Oct. 1964. Density and Composition of Mantle and Core. J. Geophys. Res. 69, 4377–4388.
- Buland, R., Chapman, C., 1983. The computation of seismic travel times.
 Bull. Seismol. Soc. Am. 73, 1271–1301.
- Calvet, M., Chevrot, S., 2005. Traveltime sensitivity kernels for PKP phases
 in the mantle. Phys. Earth Planet. Inter. 153, 21–31.
- Canup, R. M., Asphaug, E., Aug. 2001. Origin of the Moon in a giant impact
 near the end of the Earth's formation. Nature 412, 708–712.

- ⁸⁰⁷ Chenet, H., Lognonné, P., Wieczorek, M., Mizutani, H., Mar. 2006. Lateral
 ⁸⁰⁸ variations of lunar crustal thickness from the Apollo seismic data set. Earth
 ⁸⁰⁹ and Planetary Science Letters 243, 1–14.
- ⁸¹⁰ Cheng, C. H., Toksoz, M. N., Feb. 1978. Tidal stresses in the moon. J.
 ⁸¹¹ Geophys. Res. 83, 845–853.
- Chevrot, S., 2002. Optimal waveform and delay time analysis by simulated
 annealing. Geophys. J. Int. 151, 164–171.
- Dziewonski, A., Anderson, D., 1981. Preliminary reference Earth model.
 Phys. Earth Planet. Inter. 25, 297–356.
- Efron, B., Tibshirani, R., 1993. An introduction to the bootstrap. CRC Press,
 monographs on Statistics and Applied Probability Series.
- Gagnepain-Beyneix, J., Lognonné, P., Chenet, H., Lombardi, D., Spohn,
 T., Dec. 2006. A seismic model of the lunar mantle and constraints on
 temperature and mineralogy. Physics of the Earth and Planetary Interiors
 159, 140–166.
- Goossens, S., Matsumoto, K., Jan. 2008. Lunar degree 2 potential Love number determination from satellite tracking data. GRL 35, 2204-+.
- Hood, L. L., Jones, J. H., Mar. 1987. Geophysical constraints on lunar bulk
 composition and structure A reassessment. J. Geophys. Res. 92, 396-+.
- Hood, L. L., Mitchell, D. L., Lin, R. P., Acuna, M. H., Binder, A. B., Aug.
 1999. Initial measurements of the lunar induced magnetic dipole moment
 using Lunar Prospector magnetometer data. Geophys. Res. Lett. 26, 2327–
 2330.
- Kennett, B., Engdahl, E., 1991. Traveltimes for global earthquake location
 and phase identification. Geophys. J. Int. 105, 429–465.
- Khan, A., Connolly, J. A. D., Maclennan, J., Mosegaard, K., Jan. 2007. Joint
 inversion of seismic and gravity data for lunar composition and thermal
 state. Geophysical Journal International 168, 243–258.
- Khan, A., Mosegaard, K., Jun. 2002. An inquiry into the lunar interior: A
 nonlinear inversion of the Apollo lunar seismic data. Journal of Geophysical
 Research (Planets) 107, 5036-+.

- Khan, A., Mosegaard, K., Nov. 2005. Further constraints on the deep lunar
 interior. Geophys. Res. Lett. 32, 22203-+.
- Khan, A., Mosegaard, K., Williams, J. G., Lognonné, P., Sep. 2004. Does
 the Moon possess a molten core? Probing the deep lunar interior using
 results from LLR and Lunar Prospector. Journal of Geophysical Research
 (Planets) 109, 9007-+.
- Konopliv, A. S., Asmar, S. W., Carranza, E., Sjogren, W. L., Yuan, D. N.,
 Mar. 2001. Recent Gravity Models as a Result of the Lunar Prospector
 Mission. Icarus 150, 1–18.
- Koyama, J., Nakamura, Y., 1980. Focal mechanism of deep moonquakes. In:
 S. A. Bedini (Ed.), Lunar and Planetary Science Conference Proceedings.
 Vol. 11 of Lunar and Planetary Science Conference Proceedings. pp. 1855–1865.
- Kuskov, O. L., Kronrod, V. A., May 1998. Constitution of the Moon5. Constraints on composition, density, temperature, and radius of a core. Physics
 of the Earth and Planetary Interiors 107, 285–306.
- Kuskov, O. L., Kronrod, V. A., Hood, L. L., Mar. 2002. Geochemical Constraints on the Seismic Properties of the Lunar Mantle. In: Lunar and
 Planetary Institute Science Conference Abstracts. Vol. 33 of Lunar and
 Planetary Institute Science Conference Abstracts. pp. 1501-+.
- Larose, E., Khan, A., Nakamura, Y., Campillo, M., Aug. 2005. Lunar subsurface investigated from correlation of seismic noise. Geophys. Res. Lett.
 32, 16201-+.
- Lognonné, P., 2005. Planetary Seismology. Ann. Rev. Earth Planet. Sciences
 33, 19.1–19.34.
- Lognonné, P., Beyneix, J. G., Banerdt, W. B., Cacho, S., Karczewski, J. F.,
 Morand, M., Nov. 1996. Ultra broad band seismology on InterMarsNet.
 Planet. Space Sci. 44, 1237–1249.
- Lognonné, P., Gagnepain-Beyneix, J., Chenet, H., Jun. 2003. A new seismic model of the Moon: implications for structure, thermal evolution and
 formation of the Moon. Earth and Planetary Science Letters 211, 27–44.

Lognonné, P., Giardini, D., Banerdt, B., Gagnepain-Beyneix, J., Mocquet,
A., Spohn, T., Karczewski, J. F., Schibler, P., Cacho, S., Pike, W. T.,
Cavoit, C., Desautez, A., Favède, M., Gabsi, T., Simoulin, L., Striebig, N.,
Campillo, M., Deschamp, A., Hinderer, J., Lévéque, J. J., Montagner, J. P.,
Rivéra, L., Benz, W., Breuer, D., Defraigne, P., Dehant, V., Fujimura,
A., Mizutani, H., Oberst, J., Oct. 2000. The NetLander very broad band
seismometer. Planet. Space Sci. 48, 1289–1302.

Lognonné, P., Johnson, C., Dec. 2007. Planetary Seismology. Treatise on
Geophysics 10, 69–122.

Margerin, L., Campillo, M., van Tiggelen, B. A., Hennino, R., May 2009.
Energy partition of seismic coda waves in layered media: theory and application to Pinyon Flats Observatory. Geophysical Journal International 177, 571–585.

Mueller, S., Taylor, G. J., Phillips, R. J., Jun. 1988. Lunar composition - A geophysical and petrological synthesis. J. Geophys. Res. 93, 6338–6352.

Nakamura, Y., 1978. A1 moonquakes - Source distribution and mechanism.
In: Lunar and Planetary Science Conference Proceedings. Vol. 9 of Lunar
and Planetary Science Conference Proceedings. pp. 3589–3607.

- Nakamura, Y., Jan. 1983. Seismic velocity structure of the lunar mantle. J.
 Geophys. Res. 88, 677–686.
- Nakamura, Y., Duennebier, F. K., Latham, G. V., Dorman, H. J., Sep. 1976.
 Structure of the lunar mantle. J. Geophys. Res. 81, 4818–4824.
- Nakamura, Y., Koyama, J., Jun. 1982. Seismic Q of the lunar upper mantle.
 J. Geophys. Res. 87, 4855–4861.
- Nakamura, Y., Latham, G. V., Dorman, H. J., 1982. Apollo lunar seismic
 experiment Final summary. In: W. V. Boynton & T. J. Ahrens (Ed.),
 Lunar and Planetary Science Conference Proceedings. Vol. 13 of Lunar
 and Planetary Science Conference Proceedings. pp. 117-+.
- Neal, C. R., Banerdt, W. B., Alkalai, L., Mar. 2010. LUNETTE: Establishing a Lunar Geophysical Network Without Nuclear Power Through a

- ⁸⁹⁹ Discovery-Class Mission. In: Lunar and Planetary Institute Science Con-⁹⁰⁰ ference Abstracts. Vol. 41 of Lunar and Planetary Institute Science Con-⁹⁰¹ ference Abstracts. pp. 2710-+.
- Neidell, N. S., Taner, T. M., 1971. Semblance and other coherency measures
 for multichannel data. Geophysics 36, 482–497.
- Nuttli, O., 1961. The effect of the earth's surface on the S wave particle motion. Bull. Seismol. Soc. Am. 51, 237–246.
- Oldham, R. D., Feb. 1914. The Constitution of the Interior of the Earth as
 Revealed by Earthquakes. Nature 92, 684–685.
- Russell, C. T., Coleman, Jr., P. J., Goldstein, B. E., 1982. Measurements of
 the lunar induced magnetic moment in the geomagnetic tail Evidence for
 a lunar core. In: R. B. Merrill & R. Ridings (Ed.), Lunar and Planetary
 Science Conference Proceedings. Vol. 12 of Lunar and Planetary Science
 Conference Proceedings. pp. 831–836.
- Sambridge, M., Aug. 1999. Geophysical inversion with a neighbourhood
 algorithm-I. Searching a parameter space. Geophysical Journal International 138, 479–494.
- Sanloup, C., Fiquet, G., Gregoryanz, E., Morard, G., Mezouar, M., Apr.
 2004. Effect of Si on liquid Fe compressibility: Implications for sound
 velocity in core materials. Geophys. Res. Lett. 31, 7604-+.
- Sanloup, C., Guyot, F., Gillet, P., Fiquet, G., Mezouar, M., Martinez, I.,
 2000. Density measurements of liquid Fe-S alloys at high-pressure. Geophys. Res. Lett. 27, 811–814.
- Sens-Schönfelder, C., Larose, E., Oct. 2008. Temporal changes in the lunar
 soil from correlation of diffuse vibrations. Phys. Rev. E. 78 (4), 045601-+.
- Tanaka, S., Shiraishi, H., Kato, M., Okada, T., group of Post SELENE Missions, S. W., 2008. The science objectives of the SELENE-II mission as
 the post SELENE mission. Adv. Space Res. 42, 394–401.
- Tarantola, A., 1987. Inverse Problem Theory. Elsevier Science Publishers,
 B.V., Amsterdam.

- Toksoz, M. N., Dainty, A. M., Solomon, S. C., Anderson, K. R., Nov. 1974.
 Structure of the moon. Reviews of Geophysics and Space Physics 12, 539– 567.
- Vinnik, L., Chenet, H., Gagnepain-Beyneix, J., Lognonne, P., Aug. 2001.
 First seismic receiver functions on the Moon. Geophys. Res. Lett. 28, 3031– 3034.
- von Rebeur-Paschwitz, E., Jul. 1889. The Earthquake of Tokio, April 18,
 1889. Nature 40, 294–295.

Weber, R. C., Bills, B. G., Johnson, C. L., May 2009. Constraints on deep
moonquake focal mechanisms through analyses of tidal stress. Journal of
Geophysical Research (Planets) 114, 5001-+.

- Weber, R. C., Lin, P., Garnero, E. J., Williams, Q., Lognonné, P., Jan. 2011.
 Seismic Detection of the Lunar Core. Science 331, 309–.
- Wieczorek, M., Jolliff, B., Khan, A., Pritchard, M., Weiss, B., Williams, J.,
 Hood, L., Righter, K., Neal, C., Shearer, C., McCallum, I., Tompkins, S.,
 Hawke, B., Peterson, C., Gillis, J., Bussey, B., 2006. The constitution and
 structure of the lunar interior. Rev. Min. Geochem. 60, 221–364.
- Williams, J. G., Feb. 2007. A scheme for lunar inner core detection. Geophys.
 Res. Lett. 34, 3202-+.
- Williams, J. G., Boggs, D. H., Yoder, C. F., Ratcliff, J. T., Dickey, J. O.,
 Nov. 2001. Lunar rotational dissipation in solid body and molten core. J.
 Geophys. Res. 106, 27933–27968.